UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/800,731	03/16/2004	Jimmy S. Wong	58268.00302	1038
	7590 04/11/200 DERS & DEMPSEY I	EXAMINER		
8000 TOWERS CRESCENT DRIVE			NGUYEN, ANH NGOC M	
14TH FLOOR VIENNA, VA 2	22182-2700		ART UNIT	PAPER NUMBER
			2616	
			MAIL DATE	DELIVERY MODE
			04/11/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/800,731	WONG, JIMMY S.
Office Action Summary	Examiner	Art Unit
	Anh Ngoc Nguyen	2616
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet with the o	correspondence address
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D. - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period. - Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION .136(a). In no event, however, may a reply be tind d will apply and will expire SIX (6) MONTHS from te, cause the application to become ABANDONE	N. nely filed the mailing date of this communication. ED (35 U.S.C. § 133).
Status		
Responsive to communication(s) filed on 16 № This action is FINAL . 2b) This 3) Since this application is in condition for allowed closed in accordance with the practice under	is action is non-final. ance except for formal matters, pro	
Disposition of Claims		
4) Claim(s) 1-18 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) Claim(s) is/are allowed. 6) Claim(s) 1-18 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/o	awn from consideration.	
9)☐ The specification is objected to by the Examin	er.	
10) ☐ The drawing(s) filed on 03/16/2004 is/are: a) ☐ Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the E	☑ accepted or b)☐ objected to by e drawing(s) be held in abeyance. Se ction is required if the drawing(s) is ob	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority document application from the International Bureat* See the attached detailed Office action for a list	nts have been received. nts have been received in Applicat ority documents have been receive au (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail D 5) Notice of Informal F 6) Other:	ate

Art Unit: 2616

Response to Amendment

Examiner acknowledges receipt of Applicant's Arguments/Remarks dated 01/24/2008.

Claims 1 - 18 are pending.

Applicant's arguments with respect to claims 1 - 18 have been considered but are moot in view of the new ground(s) of rejection.

DETAILED ACTION

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1, 3 8, 10 15, and 17 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Brown (US 6,754,211) in view of Roy et al (US 6,246,682).

Brown discloses method and apparatus for wire speed IP multicast forwarding comprising the following features:

Regarding claim 1, Brown discloses a method of replicating multicast datagrams in a network device (see Fig. 1, switch), said method comprising: determining whether a scheduled outgoing datagram (see Fig. 1 and col. 3 lines 20 – 32, MFI corresponding to the IP multicast group to which the IP multicast data packet is to be forwarded) stored in a main memory is a multicast (MC) packet (see col. 4 lines 31 – 35, identifying the received IP multicast data packet); when the scheduled outgoing datagram type is the MC datagram (see col. 2 lines 52 – 62 and col. 4 lines 31 – 35 and col. 8 lines 29 - 34): performing a lookup of a replicate count

table to determine a copy count value (see col. 7 lines 9 - 22, port queue count) and writing the copy count value to a copy count register (see col. 7 lines 14 - 16, stored in a port queue counter register); awaiting a ready signal from an egress port of the network switch (see Fig. 1, Fig. 4 and col. 6 lines 31 - 40, egress multicast forwarding logic waiting signal from forward vector); sending the outgoing datagram to the egress port from the main memory along with the copy count value (see col. 1 lines 25 - 28 lines 40 - 45, forwarding IP multicast data packet and the number of copies); changing the copy count value in the copy count register (see col. 7 lines 19 - 21, port queue count is decremented therefore changing the value); modifying a VLAN identifier of the outgoing datagram (see col. 1 lines 65 - 67 col. 2 lines 1 - 10, modification entry includes an id for a Virtual LAN) if necessary based on the copy count value (see col. 7 lines 1 - 20, counter register); and forwarding the outgoing datagram from the egress port (see col. 6 lines 14 - 21, forwarding through the egress port).

Regarding claims 5 and 12, Brown discloses wherein the step of sending the outgoing datagram comprises: reading a first portion of the datagram from the main memory (see Fig. 1, memory 116); sending the first portion, along with the copy count value and the pointer (see col. 1 lines 25 – 28 lines 40 - 45, forwarding IP multicast data packet and the number of copies), to the egress port; continuing to read and send subsequent portions of the datagram until a last portion is read (see Fig. 1 and col. 4 lines 45 - 63, data-out 124 from memory 116); and decrementing the copy count value in the copy count register (see col. 7 lines 19 – 21, port queue count is decremented therefore changing the value).

Regarding claims 6 and 13, Brown discloses wherein the step of modifying the VLAN identifier of the outgoing datagram comprises accessing a VLAN ID table (see Fig. 7 VLAN ID

Art Unit: 2616

table 702) using the pointer as an index to obtain a new VLAN identifier (see Fig. 3B and col. 12 lines 12 – 26 lines 55 - 60, VLAN ID in a packet).

Regarding claims 7 and 14, Brown discloses wherein the new VLAN identifier (see Fig. 3B, VLAN ID in a packet) is obtained from a bit value in an entry in the VLAN ID table (see Fig. 7 VLAN ID table 702) provided by the pointer (see col. 12 lines 12 – 39, an index to a VLAN ID entry), where the bit value is equal to the copy count value (see col. 7 lines 9 – 22, counter register).

Regarding claim 8, Brown discloses a network device for handling datagrams in a network (see Fig. 1, switch), comprising: a main memory (see Fig. 1, memory 116); determining means for determining whether a scheduled outgoing datagram stored in the main memory is a multicast (MC) datagram (see col. 4 lines 31 - 35, identifying the received IP multicast data packet); performing means for performing a lookup of a replicate count table to determine a copy count value (see col. 7 lines 9 - 22, port queue count) and writing the copy count value to a copy count register (see col. 7 lines 14 - 16, stored in a port queue counter register); awaiting means for awaiting a ready signal from an egress port of the network switch (see Fig. 1, Fig. 4 and col. 6 lines 31 – 40, egress multicast forwarding logic waiting signal from forward vector); sending means for sending the outgoing datagram to the egress port from the main memory along with the copy count value (see col. 1 lines 25 - 28 lines 40 - 45, forwarding IP multicast data packet and the number of copies); changing means for changing the copy count value in the copy count register (see col. 7 lines 19 - 21, port queue count is decremented therefore changing the value); modifying a VLAN identifier of the outgoing datagram (see col. 1 lines 65 - 67 col. 2 lines 1 - 10, modification entry includes an id for a Virtual LAN) if

Art Unit: 2616

necessary based on the copy count value (see col. 7 lines 9-22, counter register); and forwarding means for forwarding the outgoing datagram from the egress port (see col. 6 lines 14-21, forwarding through the egress port) wherein the performing, awaiting, sending, changing, modifying and forwarding means are configured to be activated when the scheduled outgoing datagram type is the MC datagram (see abstract, IP multicast packet).

Regarding claim 15, Brown discloses a network device for handling datagrams (see Fig. 1, switch), comprising: at least one data port interface, said at least one data port interface supporting a plurality of data ports transmitting and receiving datagrams (see Fig. 1, port 108, port 1, port 2....); in communication with said at least one data port interface; and a main memory (see Fig. 1, memory 116 coupled to ports 108, 1, 2, ...), said main memory communicating with said at least one data port interface (see Fig. 1, memory 116 coupled to ports 108, 1, 2,), configured to determine whether a scheduled outgoing datagram stored in the main memory is a multicast (MC) datagram (see col. 4 lines 31 - 35, identifying the received IP multicast data packet); wherein when the scheduled outgoing datagram is of a type that is the MC datagram (see col. 2 lines 52 - 62 and col. 4 lines 31 - 35 and col. 8 lines 29 -34), configured to perform a lookup of a replicate count table to determine a copy count value (see col. 7 lines 9 - 22, port queue count), configured to write the copy count value to a copy count register (see col. 7 lines 14 - 16, stored in a port queue counter register); configured to send the outgoing datagram to the egress port from the main memory along with the copy count value (see col. 1 lines 25 – 28 lines 40 - 45, forwarding IP multicast data packet and the number of copies), configured to change the copy count value in the copy count register (see col. 7 lines 19 – 21, port queue count is decremented therefore changing the value); and wherein the at least Art Unit: 2616

one data port interface is configured to modify a VLAN identifier of the outgoing datagram (see col. 1 lines 65 - 67 col. 2 lines 1 - 10, modification entry includes an id for a Virtual LAN) if necessary based on the copy count value (see col. 7 lines 9 - 22, counter register) and configured to forward the outgoing datagram from the egress port (see col. 6 lines 14 - 21, forwarding through the egress port).

Brown discloses the claimed limitations as stated above. Brown does not specifically disclose regarding claims 1 and 8, determining by a memory management unit; regarding claims 3 and 10, further comprising steps of waiting until the copy count value in the copy count register is zero and releasing a pointer to a memory location of the outgoing datagram in the main memory; regarding claims 4 and 11, wherein the step of performing the lookup of the replicate count table comprises determining a pointer based on the group number and using that pointer as an index for the replicate count table to perform the lookup; regarding claim 15, a memory management unit, controlling by the memory management unit; regarding claim 17, wherein the memory management unit is configured to wait until the copy count value in the copy count register is zero before releasing a pointer to a memory location of the outgoing datagram in the main memory; regarding claim 18, wherein the memory management unit is configured to determine a pointer based on a group number and configured to implement that pointer as an index for the replicate count table to perform the lookup.

Roy discloses method and apparatus for managing multiple ATM cell queues comprising the following features:

Regarding claims 1 and 8, Roy discloses determining by a memory management unit (see abstract, management memory).

Art Unit: 2616

Regarding claims 3 and 10, Roy discloses further comprising steps of waiting until the copy count value in the copy count register is zero (see abstract, reduced to zero) and releasing a pointer to a memory location of the outgoing datagram in the main memory (see abstract and col. 3 lines 20 - 33, added to the free list).

Regarding claims 4 and 11, Roy discloses wherein the step of performing the lookup of the replicate count table comprises determining a pointer based on the group number (see col. 2 lines 58 - 67, a count of the number cells in the queue) and using that pointer as an index for the replicate count table to perform the lookup (see col. 3 lines 1 - 12 and col. 4 lines 55 - 67, pointer is provided for each data element).

Regarding claim 15, Roy discloses a memory management unit (see abstract, management memory), controlling by the memory management unit (col. 3 lines 13 - 35 and col. 4 lines 39 - 43, a management RAM for managing the shared RAM).

Regarding claim 17, Roy discloses wherein the memory management unit is configured to wait until the copy count value in the copy count register is zero (see abstract, reduced to zero) before releasing a pointer to a memory location of the outgoing datagram in the main memory (see abstract and col. 3 lines 20 - 33, added to the free list).

Regarding claim 18, Roy discloses wherein the memory management unit is configured to determine a pointer based on a group number (see col. 2 lines 58 - 67, a count of the number cells in the queue) and configured to implement that pointer as an index for the replicate count table to perform the lookup (see col. 3 lines 1 - 12 and col. 4 lines 55 - 67, pointer is provided for each data element).

Art Unit: 2616

It would have been obvious to one ordinary skilled in the art at the time the invention was made to modify the invention of Brown, and use a management memory, as taught by Roy, thus providing for an efficient data storage, as discussed by Roy (see col. 2 lines 6 - 20).

3. Claims 2, 9 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Brown (US 6,754,211) in view of Roy et al (US 6,246,682) and further in view of Headrick et al (5,724,358).

Brown and Roy disclose the claimed limitations as stated in paragraph 2. Brown and Roy do not specifically disclose the following features: regarding claim 2, wherein the method performed by the memory management unit is suspended based on a presence of a higher-priority outgoing datagram; regarding claim 16, wherein the memory management unit is configured to suspend the replication of the outgoing datagram based on a presence of a higher-priority outgoing datagram.

Headrick discloses high speed packet switched digital switch and method comprising the following features:

Regarding claims 2 and 9, Headrick discloses wherein the method performed by the memory management unit is suspended based on a presence of a higher-priority outgoing datagram (see col. 2 lines 30 - 40, accepting or rejecting a data packet per priority level basis).

Regarding claim 16, Headrick discloses wherein the memory management unit is configured to suspend the replication of the outgoing datagram based on a presence of a higher-priority outgoing datagram (see col. 2 lines 30 - 40, accepting or rejecting a data packet per priority level basis).

Art Unit: 2616

It would have been obvious to one ordinary skilled in the art at the time the invention was made to modify the invention of Brown and Roy, and determine priority, as taught by Headrick, thus providing for an efficient high speed packet switched digital switch, as discussed by Headrick (see col. 2 lines 10 - 15).

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Anh Ngoc Nguyen whose telephone number is (571) 270-5139. The examiner can normally be reached on M - F, from 7AM to 3PM (alternate first Friday off).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Kwang Yao can be reached on 5712723182. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Art Unit: 2616

04/08/2008

/Kwang B. Yao/ Supervisory Patent Examiner, Art Unit 2616